

Features and Benefits

Rotary Tillers, Standard Tine Rotation

RTA10 Series

Features		Benefits		
Working widths		42", 50", 58" to meet a wide range of applications and needs.		
Gearbox Warranty		5 Years on housing, gears, seals, and bearings. Shows our confidence in the product.		
Tractor HP range		17-25 HP		
Fits Land Pride Quick-Hitch		Allows for quick and easy one person hook-up. Does not offset with Quick-Hitch.		
Formed and reinforced rear deflector		Keeps dirt in and leaves a level finish. Forming gives deflector additional strength. Adjustable deflector allows for various finish results.		
Clevis hitch		Provides additional strength and easy one person hook-up.		
Adjustable lower hitches		Offset unit to cover right tire track.		
Skid shoes		Control depth with seven adjustments.		
6 1/2" Digging depth		For deep soil penetration.		
Adjustable Parking stand		Easy hook-up and storage.		
Plate steel hitch		Plate steel is stronger than flat bar type hitch		
4 'C' shaped tines per flange		'C' Shaped tines require less HP to move through the ground.		
Solid rotor shaft		1 3/4" Solid steel rotor shaft for strength.		
15" Rotor swing diameter		For deep tilling and turning the soil over faster.		
#80 Drive chain enclosed in oil bath		Heavy drive chain stretches less, and oil bath keeps wear to a minimum.		
Stamped chain cover		Stamped forming gives the chain cover strength.		
Fully shielded shear pin or slip-clutch driveline		Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.		
American made		Many tillers are imported. American made means better parts availability.		
Double lip seal on rotor bearing		Double lip seal helps keep the dirt out and the grease in.		
Offset Dimensions	42" width	16"-26" std.	13"-29" Maximum Right	23"-19" Maximum Left
	50" width	25"-25" std.	18"-32" Maximum Right	32"-18" Maximum Left
	58" width	29"-29" std.	22"-36" Maximum Right	36"-22" Maximum Left

Designs, specifications, features and information are subject to change without notice.

Features and Benefits

Rotary Tillers, Standard Tine Rotation

RTA15 Series

Features	Benefits
Working widths	50", 58" to meet specific customer needs.
Tractor HP range	17 - 35 HP
Gearbox warranty	5 Year on housing, gears, seals and bearings. Shows our confidence in the product.
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up. Cannot be used with sideshift.
Sideshift capabilities	Sideshift tiller to cover right tire track. Gearbox slides with tiller.
Sideshift dimensions 50"	25-25 Std.; 12-38 Max. right; 31-19 Max. left
Sideshift dimensions 58"	29-29 Std.; 12-46 Max. right; 35-12 Max. left
Formed and reinforced rear deflector	Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
Clevis hitch	Provides additional strength and easy one person hook-up.
Skid Shoes	Control depth with various settings.
6 1/2" Digging depth	For deep soil penetration.
Adjustable Parking Stand	Easy hook-up and storage.
Plate steel hitch	Plate steel is stronger than flat bar type hitch.
4 'C' Shaped heat-treated tines per flange	'C' Shaped tines require less HP to move through the ground.
Solid rotor shaft	1 3/4" Solid steel shaft for strength.
Cat. 3 Driveline	Cat. 3 Driveline with heavy-duty shear-bolt or slip-clutch
15" Rotor swing diameter	For deep tilling and turning the soil over faster.
Double lip seal on rotor bearing	Double lip seal helps keep the dirt out and the grease in.
#80 Drive chain enclosed in oil bath	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
Stamped chain cover	Stamped forming gives the chain cover strength.
Fully shielded shear pin or slip-clutch driveline	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.

Designs, specifications, features and information are subject to change without notice.